

ALEMANOL

german lubricants



ALEMANOL 2T Profi

Alemanol 2T Profi is a premium grade synthetic engine oil specially designed for the latest high performance two-stroke engines of various brands.

DESCRIPTION

Due to its almost residue-free and extremely low-smoke emission it offers the best protection against wear and deposits. It has moreover a high stability even at high-temperature. Alemanol 2T Profi is suitable for all heavy loaded air and water-cooled two-stroke petrol engines such as mopeds, scooters, lawnmowers, chain saws, power generators and many more. It is also suitable for separate lubrication. Due to the special selection of additives, it is formulated to exceed the requirements of all leading engine manufacturers.

BENEFITS

- highest wear protection due to excellent
- excellent lubricity
- good stability at high temperature
- Optimum engine cleanliness due to intensive cleaning effect
- protection against deposits
- avoidance of spark plug bridges
- best oxidation stability

Recommended and tested in units for which the following specifications and filling instructions are required:

API TC
GLOBAL GD
ISO EGD
JASO FD
T.I.S.I.

Honda DIO AF 27
Kawasaki KH 125M
Suzuki SX 800R
Yamaha CE 50S
Yamaha RD 350B
Husqvarna 242

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,86
Viscosity 40°C	DIN 51562	mm ² /s	59
Viscosity 100°C	DIN 51562	mm ² /s	10
Viscosity Index	DIN 2909	-	160
Flash Point	DIN ISO 2592	°C	185
Pourpoint	DIN ISO 3016	°C	-25

Use in accordance with engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 19.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal