

ALEMANOL

german lubricants



ALEMANOL 2T Super

Alemanol 2T Super is a premium class engine oil specially designed for the latest high-performance two-stroke engines of various brands.

DESCRIPTION

With its virtually residue-free and extremely low-smoke combustion, it offers the best protection against wear, deposits and sludge formation. In addition, it offers above-average stability at high temperatures. Alemanol 2T Super is suitable for all normally loaded air- and water-cooled two-stroke gasoline engines such as mopeds, mopeds, lawn mowers, chain saws, power generators, and many more. Also suitable for separate lubrication.

BENEFITS

- highest wear protection due to excellent lubricity
- good stability at high temperature
- hardly any smoke development
- Optimum engine cleanliness due to intensive cleaning effect
- protection against deposits
- avoidance of spark plug bridges
- best oxidation stability

Recommended and tested in units for which the following specifications and filling instructions are required:

API TC
GLOBAL GC
ISO EGC
JASO FC
T.I.S.I.

Kawasaki KH 125M
Yamaha CE 50S
Yamaha RD 350B
Suzuki SX 800R

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,87
Viscosity 40°C	DIN 51562	mm ² /s	66
Viscosity 100°C	DIN 51562	mm ² /s	9,5
Viscosity Index	DIN 2909	-	125
Flash Point	DIN ISO 2592	°C	150
Pourpoint	DIN ISO 3016	°C	-20

Use in accordance with engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 19.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal