

ALEMANOL

german lubricants



ALEMANOL C-3 XP 5W-30

Alemanol C-3 XP 5W-30 is a top-class passenger car engine oil specially designed for the most modern high-performance engines of leading German brands. In addition, however, it can also be used in Asian models that have a corresponding classification according to ACEA.

DESCRIPTION

It provides field-proven protection against wear, deposits and sludge, with the best possible protection of particulate or oxidation filters at the same time. Alemanol C-3 XP 5W-30 was developed to sustainably improve the fuel economy of vehicles. It optimizes the service life of exhaust aftertreatment systems, such as catalytic converters or soot particle filters, and can be used at extended maintenance intervals.

BENEFITS

- Excellent wear protection
- optimization of the service life of exhaust gas aftertreatment systems
- low oil consumption
- Reduction of exhaust gas emission
- high operational reliability
- Reduction of fuel consumption

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 5W-30
ACEA C2/C3

BMW Longlife-04
MB 229.51, MB 229.52
VW 504.00, VW 507.00
VW 502.00, VW 505.00, VW 505.01
VW 503.00, VW 506.00, VW 506.01
Porsche C30
Fiat 9.55535-S3
Ford WSS-M2C917-A

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,85
Viscosity 40°C	DIN 51562	mm ² /s	72
Viscosity 100°C	DIN 51562	mm ² /s	12
Viscosity index	DIN 2909	-	160
Flash Point	DIN ISO 2592	°C	210
Pourpoint	DIN ISO 3016	°C	-42

Use in accordance with engine manufacturer's instructions

All key data are average values and are subject to production-related fluctuations

Rev. 18.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal