

ALEMANOL

german lubricants



ALEMANOL C-3 XP 5W-40

Alemanol C-3 XP 5W-40 is a top-class passenger car engine oil specially designed for the most modern high-performance engines of leading German brands. In addition, it can also be used in Asian models that have an appropriate classification according to ACEA.

DESCRIPTION

It provides excellent field-proven protection against wear, deposits and sludge. Alemanol C-3 XP 5W-40 was developed to make the fuel economy of vehicles more efficient and to protect components of the turbocharger. Furthermore, it optimizes the service life of exhaust aftertreatment systems, such as catalytic converters or soot particle filters.

BENEFITS

- excellent wear protection
- optimum oil pressure
- minimal friction and evaporation loss
- Optimum engine cleanliness due to intensive cleaning effect
- Reduction of exhaust gas emission
- fuel saving

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 5W-40
ACEA C3
API SN/CF

MB 229.51/MB 229.31/MB 226.5
VW 505.00, VW 505.01, VW 502.00
Porsche A40
Ford WSS-M2C917-A
BMW Longlife-04
Renault RN0700, Renault RN0710
Fiat 9.55535-S2
GM DX2 / Opel DX2
For all Opel engines from year of manufacture 2010 backwards compatible with GM-LL-A-025 as well as GM-LL-B-025 (years of manufacture before 2010)

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,85
Viscosity 40°C	DIN 51562	mm ² /s	76
Viscosity 100°C	DIN 51562	mm ² /s	14
Viscosity index	DIN 2909	-	170
Flash Point	DIN ISO 2592	°C	218
Pourpoint	DIN ISO 3016	°C	-38

Use in accordance with engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 18.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal