

ALEMANOL

german lubricants



ALEMANOL Eurotruck CK-4 15W-40

Alemanol Eurotruck CK-4 15W-40 is a premium class commercial vehicle engine oil, specially developed for the latest high performance engines.

DESCRIPTION

Due to outstanding oxidation stability, aging stability and smooth running characteristics, it offers maximum fuel economy as well as excellent protection against wear, deposits and sludge formation. The application profile meets the long change intervals of the vehicle manufacturers and represents the current state of the art. Alemanol Eurotruck CK-4 15W-40 was designed to guarantee the fuel economy of vehicles and to meet all valid specifications.

BENEFITS

- high wear protection
- very good viscosity-temperature behavior
- very good cold start properties
- fuel economy
- high engine cleanliness
- high oxidation and aging resistance

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 15W-40
ACEA E9/E7
API CK-4, CJ-4/SN

MAN M3275, MAN M3575
MB 228.31
MTU DDC Type 2.1
Ford WSS-M2C171-E
Mack EO-O Premium Plus
Mack EO-S-4.5
Renault RLD-3, Renault RLD-4

Volvo VDS-4.5, Volvo VDS-4
Ford WSS-M2C171-F1
Cummins CES 20081
Cummins CES 20086
Cummins CES 20087
Caterpillar ECF-3
Detroit Diesel DDC 93K218
Detroit Diesel DDC 93K222
Detroit Diesel DDC 93K223
Deutz DQC III-10 LA
John Deere JDQ 78-X

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,87
Viscosity 40°C	DIN 51562	mm ² /s	111
Viscosity 100°C	DIN 51562	mm ² /s	14,5
Viscosity Index	DIN 2909	-	151
Flash Point	DIN ISO 2592	°C	225
Pourpoint	DIN ISO 3016	°C	-28

Use in accordance with engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 19.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal