

# ALEMANOL

german lubricants



## ALEMANOL Eurotruck LA 5W-30

Alemanol Eurotruck LA 5W-30 is a premium class commercial vehicle engine oil, specially developed for the latest high performance engines.

### DESCRIPTION

Due to optimum oxidation stability and aging stability, it offers maximum fuel economy, high protection against wear, deposits and sludge and extends the change interval outstandingly proven in practice. Alemanol Eurotruck LA 5W-30 has been designed to significantly improve the fuel economy of vehicles to protect turbocharger components as well as to represent rationalized applications.

### BENEFITS

- most modern "Low SAPS" - additive technology
- suitable for longest oil change intervals
- excellent wear protection even under high load
- fuel saving
- best protection for modern exhaust aftertreatment systems
- high oxidation and aging resistance

**Recommended and tested in units for which the following specifications and filling instructions are required:**

SAE 5W-30  
ACEA E7/E6  
API CI-4

MAN M 3477, MAN M 3271-1  
MB 228.51  
Volvo VDS-3  
Mack EO-N, Mack EO-M  
Caterpillar ECF-1a  
Cummins CES 20077, Cummins CES 20076  
MTU DDC Type 3.1  
Renault RDL-2, Renault RXD, Renault RGD  
Iveco 18-1804 TLS-E6  
Scania LA  
DAF

### TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,865
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	69,9
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	11,1
Viscosity index	DIN 2909	-	160
Flash point	DIN ISO 2592	°C	218
Pourpoint	DIN ISO 3016	°C	-35

Use in accordance with engine manufacturer's instructions  
All key data are average values and are subject to production-related fluctuations

Rev. 04.03.2021

TRIBUTECH GmbH  
Windhauser Weg 2 - 41366 Schwalmtal