

ALEMANOL

german lubricants



ALEMANOL Truck XP 10W-40

Alemanol Truck XP 10W-40 is a top-class super long-life engine oil specially designed for use in all diesel vehicles with and without turbocharging. It also covers a large part of the requirements of cars, trucks, buses and work machines. It fully ensures trouble-free year-round use without restrictions.

DESCRIPTION

Alemanol Truck XP 10W-40 offers optimal oxidation stability and aging stability as well as high protection against wear and deposits, even in short-distance traffic, thanks to its high additivation. At the same time, the large performance reserve offers further advantages, even with higher sulfur contents of the diesel fuel. It keeps sludge out and extends the change interval. Alemanol Truck XP 10W-40 was designed to positively contribute to the fuel economy of motor vehicles without exhaust aftertreatment, to protect components of the turbocharger and to combine rationalizing applications.

ADVANTAGES

- very high wear protection, even under higher loads
- very good viscosity-temperature behavior
- very appealing cold start properties
- high operational reliability
- excellent aging and corrosion protection
- very high engine cleanliness

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 10W-40
ACEA A3/B4, E7
API SL/CF, CI-4
JASO DHD-1

MB 228.3, MB 229.1
MAN M3275-1
Renault RLD-2, Renault RLD
Volvo VDS-3
Iveco 18-1804 T2 E7
DAF
MTU DDC Type 2
Mack EO-N, Mack EO-M
Detroit Diesel DDC 93K215
Caterpillar ECF-2, Caterpillar ECF-1a
Cummins CES 20071, Cummins CES 20072, Cummins CES 20076, Cummins CES 20077, Cummins CES 20078
Scania LDF-2, Scania LDF
VW 501.01, VW 505.00

TECHNICAL DATA

Properties	Method	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,871
Viscosity 40°C	DIN 51562	mm ² /s	90
Viscosity 100°C	DIN 51562	mm ² /s	14
Viscosity index	DIN 2909	-	160
Flash Point	DIN ISO 2592	°C	212
Pourpoint	DIN ISO 3016	°C	-36

Use in accordance with the engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 19.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal