

# ALEMANOL

german lubricants



## ALEMANOL XP 10W-30

Alemanol XP 10W-30 is a modern fuel-efficient engine oil for all-season use and brands of various leading manufacturers. However, it can also be used in all models that have the appropriate classification.

### DESCRIPTION

It provides excellent field-proven protection against wear, deposits and sludge, its formulation with HC synthetic oils ensures very good viscosity-temperature behavior, even under adverse conditions. Alemanol XP 10W-30 is also highly recommended for use in gas-powered vehicles and diesel engines (with and without turbochargers).

### BENEFITS

- Very good shear stability
- Low oil consumption
- Smooth running characteristics
- Optimum engine cleanliness due to intensive cleaning effect
- Very good corrosion protection
- Fuel saving

**Recommended and tested in aggregates for which the following specifications and filling regulations are required:**

SAE 10W-30  
ACEA A3/B4, E3  
API SL/CF, CG-4

MB 228.1, MB 228.3, MB 229.1  
Volvo VDS, Allison C4  
MAN 3275, MAN 271  
MTU DDC Type 1, MTU DDC Type 2  
Renault RD, RGD  
VW 505.00, VW 501.01

### TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,860
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	73
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	11,5
Viscosity index	DIN 2909	-	150
Flash Point	DIN ISO 2592	°C	215
Pourpoint	DIN ISO 3016	°C	-33

Use in accordance to engine manufacturer's instructions  
All key data are average values and are subject to production-related fluctuations

Rev. 18.02.2021

TRIBUTECH GmbH  
Windhauser Weg 2 - 41366 Schwalmtal