

ALEMANOL

german lubricants



ALEMANOL XP 10W-40

Alemanol XP 10W-40 is a modern fuel-efficient engine oil for all-season use and brands of a wide range of leading manufacturers. However, it can also be used in all models that have a corresponding classification.

DESCRIPTION

It provides excellent field-proven protection against wear, deposits and sludge. Its formulation with HC synthetic oils ensures very good viscosity-temperature behavior, even under adverse conditions. Alemanol XP 10W-40 is also highly recommended for use in gas-powered vehicles and diesel engines (with and without turbochargers).

BENEFITS

- very good shear stability
- low oil consumption
- smooth running characteristics
- optimal engine cleanliness due to intensive cleaning effect
- very good corrosion protection
- fuel saving

Recommended and tested in aggregates for which the following specifications and filling regulations are required:

SAE 10W-40
ACEA A3/B4, E3
API SL/CF, CG-4

MB 228.1, MB 229.1
Volvo VDS, Allison C4
MAN 271
VW 505.00, VW 501.01

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,868
Viscosity 40°C	DIN 51562	mm ² /s	91,7
Viscosity 100°C	DIN 51562	mm ² /s	14,4
Viscosity index	DIN 2909	-	162
Flash Point	DIN ISO 2592	°C	220
Pourpoint	DIN ISO 3016	°C	-32

Use in accordance to engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 18.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal