

ALEMANOL

german lubricants



ALEMANOL XP 5W-40

Alemanol XP 5W-40 is a modern passenger car fuel-efficient engine oil for all-season use from a wide range of leading manufacturers. However, it can also be used in all models that have a corresponding classification.

DESCRIPTION

It provides excellent field-proven protection against wear, deposits and sludge. Its formulation with HC synthetic oils ensures very good viscosity-temperature behavior, even under adverse conditions. Alemanol XP 5W-40 is also highly recommended for use in gas-powered vehicles and diesel engines (with and without turbochargers).

BENEFITS

- very good shear stability
- low oil consumption
- smooth running characteristics
- optimal engine cleanliness due to intensive cleaning effect
- very good corrosion protection
- Proven in practice

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 5W-40
ACEA A3/B4
API SL/CF

MB 229.5/, MB 229.3, MB 229.1
Renault RN 0700
BMW Longlife-01
GM LL-A-025, GM LL-B-025
VW 505.00, VW 502.00, VW 501.01

TECHNICAL DATA

Properties	Methode	Unit	Value
Density 15°C	DIN 51757	g/ ml	0,855
Viscosity 40°C	DIN 51562	mm ² /s	84,5
Viscosity 100°C	DIN 51562	mm ² /s	14,5
Viscosity index	DIN 2909	-	143
Flash Point	DIN ISO 2592	°C	215
Pourpoint	DIN ISO 3016	°C	-42

Use in accordance with engine manufacturer's instructions
All key data are average values and are subject to production-related fluctuations

Rev. 18.02.2021

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal